



POOL DATA			
POOL CODE	20' x 42'	VOLUME	28300.00 GAL
PERIMETER	120.1 L.F.	DIAMETER	22.000' @ 16.000'
POOL AREA	840.0 SQ. FT.	DEPTH	4' @ 17.500' (CONST.)
POOL FLOOR	ARMED FLOOR CONCRETE	FINISH	ARMED CONCRETE
RETURN	2	FIXTURES	27" x 11.5" x 11.5" RETURN
POOL DEPTH	3.5' - 5' - 4'	FIXTURES	20" x 16" x 20" W/ THERM
FINISHES	EDGE & SPANNER	CONCRETE	CONCRETE

POOL FINISH ITEMS			
CONCRETE	ARMED CONCRETE	POOL AREA	5.00 SQ. YD. @ 16.000' (CONST.)
FINISH	ARMED CONCRETE	POOL AREA	5.00 SQ. YD. @ 16.000' (CONST.)
FINISH	ARMED CONCRETE	POOL AREA	5.00 SQ. YD. @ 16.000' (CONST.)
FINISH	ARMED CONCRETE	POOL AREA	5.00 SQ. YD. @ 16.000' (CONST.)

CONSTRUCTION NOTES			
1.	See Statement: This pool requires 1500 gal. of concrete based on original plans but discovered a structural issue with the existing retaining wall. Should any rock or other debris be in the way of pool excavation? They too shall be removed.	2.	The pool shall be excavated to a minimum depth of 4 feet below existing grade. The pool shall be finished with a minimum of 4" of concrete. The pool shall be finished with a minimum of 4" of concrete. The pool shall be finished with a minimum of 4" of concrete.
3.	Unless otherwise noted, the design consultant has not been required to contact. You may be contacted by the design consultant for clarification with respect to conditions as they may exist at the site below. The design consultant will provide additional data/recommendations for any existing conditions that may be present. The design consultant will provide additional data/recommendations for any existing conditions that may be present. The design consultant will provide additional data/recommendations for any existing conditions that may be present.	4.	The design consultant will provide additional data/recommendations for any existing conditions that may be present. The design consultant will provide additional data/recommendations for any existing conditions that may be present. The design consultant will provide additional data/recommendations for any existing conditions that may be present.

EQ. ROOM NOTES			
1.	A suitable equipment room shall be provided to house all pool equipment and ensure unobstructed access. The room shall be of adequate size to accommodate all equipment to be installed in the room. The room shall have a door at least 8 feet high and have a standard size lockable entrance door.	2.	Where an equipment room is constructed at a different elevation than the pool, the room shall be finished with a minimum of 4" of concrete. The room shall be finished with a minimum of 4" of concrete. The room shall be finished with a minimum of 4" of concrete.
3.	The room shall be finished with a minimum of 4" of concrete. The room shall be finished with a minimum of 4" of concrete. The room shall be finished with a minimum of 4" of concrete.	4.	The room shall be finished with a minimum of 4" of concrete. The room shall be finished with a minimum of 4" of concrete. The room shall be finished with a minimum of 4" of concrete.

ADAM M. HEATH
Listen - Design - Build
91 Prospect St.
Newmarket, ON L3Y 3T3
757-603-3686
WWW.ADAMMHEATH.COM

760 9 line south
oro-medonte, on

bluediamond
POOLS & LANDSCAPING

Scale: 3/32" = 1'
SHEET: L102